

RGB CABLE MALE TO MALE



(RGB-2MM)

RGB CABLE MALE TO FEMALE



(RGB-2MF)

**Available in various range from 2/3/5/10/15/20 MM | MF;
30/40/50MM**

- High performance VGA cable connects a VGA (Video Graphic Array) equipped computer to a monitor or projector with 15-pin VGA port (also known as RGB, DB-15, DE-15, HD-15, HDB-15 or D-sub 15) for video editing, gaming, or video projection
- Supports resolutions at 800x600 (SVGA), 1024x768 (XGA), 1600x1200 (UXGA), 1080p (Full HD), 1920x1200 (WUXGA), and up for high resolution LCD and LED monitors

- The VGA cord engineered with moulded strain relief connectors for durability, grip treads for easy plugging and unplugging, and finger-tightened screws for a secure connection
- The combination of Two Ferrite Core and bare copper conductors provides this monitor cable with superior cable performance
- Foil & braid shielding and integrated dual ferrite cores on the VGA wire minimize crosstalk, suppress noise, and protect against electromagnetic interference (EMI) and radio frequency interference (RFI)
- Supports hot plugging of VGA display devices / Two ferrites Cores to prevent signal loss.
- **Connects PC or laptop to the projector, LCD monitor, and other video display system through VGA connections**